



Article no	Description	Dimensions	A (ØID)	B (ØOD)	G (ØCTR) ±	C (flange)	L	N	Remarks
814535	TRifer_ASME BPE_1.5"	Ø034,8 inw x1,65mm C=50,5	34,7	38,1	43,6	50,5	21,5	5,0	DT-22B 2019
814487	TRifer_ASME BPE_2"	Ø047,5 inw x1,65mm C=064	47,7	50,7	56,0	64,0	21,5	5,0	DT-22B 2019
806606	TRifer_ASME BPE_2.5"	Ø060,2 inw x1,65mm C=077,5	60,3	63,5	70,5	77,5	28,5	5,0	DT-22B 2019
800758	TRifer_ASME BPE_3"	Ø072,9 inw x1,65mm C=091	72,9	76,4	83,3	91,0	28,6	6,0	DT-22B 2019
805505	TRifer_ASME BPE_4"	Ø097,38 inw x2,11mm C=119	97,4	101,6	110,0	119,0	28,6	6,5	DT-22B 2019
807506	TRifer_ASME BPE_6"	Ø146,86 inw x2,77mm C=167	146,7	152,4	156,5	167,0	28,6	8,5	
817087	TRifer_US_L1 4AM_08_US	Ø197,66 inw x2,77mm C=217,67	197,7	203,2	207,2	217,7	28,0	8,5	
817088	TRifer_US_L1 4AM_10_US	Ø248,46 inw x2,83mm C=268,47	248,5	254,0	258,0	268,5	28,0	8,5	
817089	TRifer_US_L1 4AM_12_US	Ø299,26 inw x2,83mm C=319,27	299,0	304,8	308,8	319,3	28,0	8,5	
809081	TRifer_ASME BPE_8" Spec	Ø197,66 inw x2,77mm C=217,4	197,7	203,2	207,0	217,4	28,0	8,5	
813653	TRifer_BS4825 pt3_1"	Ø022,2 inw x1,65mm C=050,5	22,0	25,4	43,6	50,5	21,5	7,0	
813648	TRifer_BS4825 pt3_1.5"	Ø034,8 inw x1,65mm C=050,5	34,7	38,1	43,6	50,5	21,5	5,0	
812651	TRifer_BS4825 pt3_2"	Ø047,6 inw x1,73mm C=064	47,4	50,9	56,0	64,0	21,5	5,0	
802621	TRifer_BS4825 pt3_2.5"	Ø060,3 inw x1,73mm C=077,5	60,3	63,5	70,5	77,5	21,5	6,0	
800916	TRifer_BS4825 pt3_3"	Ø073 inw x1,65mm C=091	73,0	76,1	83,5	91,0	21,5	6,5	
807537	TRifer_BS4825 pt3_3.5"	Ø084,7 inw x2,1mm C=106	84,5	89,9	97,5	106,0	21,5	6,5	
800563	TRifer_BS4825 pt3_4"	Ø097,6 inw x2,13mm C=119	97,6	101,6	110,2	119,0	21,5	6,5	
807538	TRifer_BS4825 pt3_5"	Ø123 inw x2mm C=144,4	123,0	127,0	134,5	144,4	28,0	6,5	
807430	TRifer_BS4825 pt3_5.5"	Ø135,76 inw x 2,4mm C=155	135,7	139,7	146,0	155,0	28,3	8,5	
807539	TRifer_BS4825 pt3_6 5/8"	Ø163,1 inw x3,13mm C=183	163,1	168,3	174,0	183,0	28,0	8,5	
807540	TRifer_BS4825 pt3_8 5/8"	Ø213,9 inw x3,33mm C=233,5	213,9	219,1	225,0	233,5	28,0	8,5	
807536	TRifer_BS4825 pt3_10 5/8"	Ø266,3 inw x3,35mm C=286,1	267,8	273,0	276,0	286,0	28,0	8,0	
803398	TRifer_BS4825 pt3_12 5/8" Stan	Ø315,93 inw x3,95mm C=338	315,9	324,0	329,0	338,0	28,0	8,5	
802896	TRifer_BS4825 pt3_12"	Ø300,8 inw x2,00mm C=319	300,8	304,8	308,0	319,0	28,0	8,5	
807072	TRifer_DIN32676_025	Ø026 inw x1,5mm C=050,5	26,0	29,0	43,6	50,5	21,5	6,5	
808893	TRifer_DIN32676_032	Ø032 inw x1,5mm C=050,5	31,9	34,9	43,6	50,5	21,5	6,0	
806321	TRifer_DIN32676_040	Ø038 inw x1,5mm C=050,5	37,9	41,0	43,6	50,5	21,5	5,0	
806322	TRifer_DIN32676_050	Ø050 inw x1,5mm C=064	50,0	53,0	56,0	64,0	21,5	5,0	
801554	TRifer_DIN32676_065	Ø065 inw x2mm C=091	65,8	70,0	83,5	91,0	28,0	6,5	
802525	TRifer_DIN32676_080	Ø080 inw x2mm C=106	81,0	85,0	97,3	106,0	28,0	7,0	
800875	TRifer_DIN32676_100	Ø100 inw x2mm C=119	100,0	104,0	110,0	119,0	28,0	6,5	
800701	TRifer_DIN32676_125_B	Ø125 inw x2mm C=155	125,0	129,0	145,7	155,0	28,0	11,0	
806728	TRifer_DIN32676_125_S	Ø125 inw x2mm C=144,4	125,0	129,0	133,6	144,4	28,0	6,5	
801059	TRifer_DIN32676_150_B	Ø150 inw x2mm C=183	150,0	154,0	174,0	183,0	28,0	11,0	
800872	TRifer_DIN32676_150_S	Ø150 inw x2mm C=167	150,0	154,0	156,0	167,0	28,1	8,0	
800385	TRifer_DIN32676_200_B	Ø200 inw x2mm C=233,5	200,0	204,0	225,0	233,5	28,0	11,0	
800386	TRifer_DIN32676_200_S	Ø200 inw x2mm C=217,5	200,0	204,0	207,0	217,4	28,2	8,5	
800279	TRifer_DIN32676_250	Ø250 inw x2mm C=268	250,0	254,0	257,5	268,0	28,0	8,0	
801432	TRifer_DIN32676_300	Ø300 inw x2mm C=319	300,0	304,0	308,5	319,0	28,0	8,0	
813654	TRifer_ISO1127_020	Ø022,9 inw x2mm C=050,5	22,8	26,9	43,6	50,5	21,5	7,0	
813655	TRifer_ISO1127_025	Ø029,7 inw x2mm C=050,5	29,6	33,8	43,6	50,5	21,5	6,0	
813656	TRifer_ISO1127_032	Ø038,4 inw x2mm C=064	38,0	42,3	56,0	64,0	21,5	6,5	
808897	TRifer_ISO1127_040	Ø044,3 inw x2mm C=064	44,1	48,4	56,0	64,0	21,5	6,0	
809087	TRifer_ISO1127_050	Ø056,3 inw x2mm C=077,5	56,3	60,3	70,5	77,5	21,5	6,0	
801977	TRifer_ISO1127_065	Ø072,1 inw x2mm C=091	72,0	76,4	83,5	91,1	21,5	6,0	
801976	TRifer_ISO1127_080	Ø084,9 inw x2mm C=106	84,8	89,0	96,8	106,0	21,5	6,5	
800735	TRifer_ISO1127_100	Ø110,3 inw x2mm C=130	110,3	114,3	122,0	130,0	28,0	6,5	
801974	TRifer_ISO1127_125	Ø135,7 inw x2mm C=155	135,7	139,7	146,0	155,0	28,3	8,5	
800736	TRifer_ISO1127_150	Ø163,1 inw x2,6mm C=183	163,1	168,3	174,0	183,0	28,0	8,5	
801042	TRifer_ISO1127_200	Ø213,9 inw x2,6mm C=233,5	213,9	219,1	225,0	233,5	28,0	8,5	
801224	TRifer_ISO1127_250	Ø267,8 inw x2,6mm C=286,1	267,8	273,0	276,0	286,0	28,0	8,0	
801975	TRifer_ISO1127_300	Ø318,7 inw x2,6mm C=338,5	318,7	324,0	328,5	338,5	28,0	8,5	